

COMPACT RULES

STOCK 106 AND UNDER

1. All doors and trunk lids may be fastened shut by wire, chains, (two per seam), or 24 inches max of weld per door or trunk lid (3 inch max wide strapping) on the outside door seams, top of trunk lid only. Drivers door may be reinforced for drivers safety. No extra welding or bracing on body seams or frames will be allowed.
2. Frames must be stock only without any added bolts or welding of seams.
3. Bumpers may be wired, chained, or bolted on. And (12) inches of weld per frame rail to bumper. No added metal, just use welder. May swap compact style bumper.
4. Cutting fenders for tire clearance is allowed, no bolting or welding.
5. Tucking the trunk lid is allowed only fastened on top only, may crease trunk 4 inches max from stock location, pinching fenders or other body panels will not be allowed, must remain stock. Any form of body creasing, body enhancing will be cut out.
6. Hoods may be fastened shut with (4 strands) wire or chain (3/8) in a max. of 6 locations, (two may go to bumper) or may be bolted with 4-3/4 bolts- 3 inch diameter max washers on top, fastened to sheet metal only (not to frame) don't add any metal. Hoods will have holes large enough for fire extinguisher access and must be open for inspection, no bolting or screws in hood openings. (All bumpers MUST have two wires or chains holding bumper from falling off) may go to hood or trunk to secure.
7. Engines may be wired, chained, in two locations, 4 or 6 cyl engine only.
8. Stock axles, with no bracing or modifying of brackets, may be welded for posi-traction. Must be 2 wheel drive, front or rear. If 4 wheel drive, either front or rear must be disabled.
9. Jody mounts, suspension, steering, and shocks must be stock only, not reinforced.
10. Transmission coolers are not allowed, may alter transmission linkage, modified ignition switches, and headers are allowed.
11. Passenger tires 6 ply max, may be snow tires with tubes, filled with air only and NOT stuffed, studded, doubled, tractor, or skid loader tires. Stem protectors allowed, wheel weights must be removed. May add an outer flap (extra sidewall) to outer side of tire for protection. May screw or glue beads to rims.
12. Fuel tanks (no plastic tanks) must be located in back seat, securely fastened, no bungee straps, and completely covered with a nonflammable material. Original gas tank must be removed. If running electric fuel pump, power source must be well labeled (fuel pump) in large bold lettering.
13. Two batteries are allowed and must be moved to passenger front seat, securely fastened, no bungee straps, and covered with a nonflammable item.
14. Safety bars in the dash and behind seat are permitted with a max. 8' x 8" mounting plate. 4 inch diameter max. material, may connect dash to seat bar with no down bars. U may run roof (halo) bar but only can be attached to seat bar, may not attach to floor, no cage material no further rearward than front side of rear wheel-well tub. Added bars in front of the driver from the front cowl up to the roof will be MANDATORY (2 WINDSHIELD BARS OR #9 WIRE) to keep hood from coming into drivers compartment, may also have driver's door window netting. No wire in any other window openings, no wire from roof to any location other than specified.
15. Boundaries will be observed at all times. No deliberate pushing out of bounds.
16. Two fires allowed before elimination.
17. Stock cooling systems only.

IF THE RULES DO NOT SAY IT DO NOT ASSUME THAT YOU CAN DO IT, THIS IS A STOCK, LOW BUDGET CLASS!!! JUDGES DECISION IS FINAL!!!